




| AP Clutch Model Number | Clutch Plates | Clutch Diameter | SAE Hsg. |
|------------------------|---------------|-----------------|----------|
| S10B3L | Single | 10.0" | 3 |
| S10B4L | Single | 10.0" | 4 |
| S10A3L | Single | 10.0" | 3 |
| S10A4L | Single | 10.0" | 4 |
| S11B2L | Single | 11.5" | 2 |
| S11B3 | Single | 11.5" | 3 |
| S11B3L | Single | 11.5" | 3 |
| S11A3L | Single | 11.5" | 3 |
| D11B1L | Double | 11.5" | 1 |
| D11B2L | Double | 11.5" | 2 |
| D11A2L | Double | 11.5" | 2 |
| D11B3L | Double | 11.5" | 3 |
| D11B3L | Double | 11.5" | 3 |
| D11B3L | Double | 11.5" | 3 |
| S14B1L | Single | 14.0" | 1 |
| S14A1L | Single | 14.0" | 1 |
| D14B1L | Double | 14.0" | 1 |
| D14A1L | Double | 14.0" | 1 |
| D14B1L-HD | Double | 14.0" | 1 |
| T14A1L8 | Triple | 14.0" | 1 |
| T14A1L8-HD | Triple | 14.0" | 1 |
| T14A1L10 | Triple | 14.0" | 1 |
| T14A1L10-HD | Triple | 14.0" | 1 |

Call Foley Engines at (800) 233-6539 to replace your .

AP Clutch Models Made Easy:

Complete standard type Power Take Off assembly.

Pilot bearing, press fit, self-aligning, sealed for life.

Universal dual tapered main bearings allow both side load and in-line drive duty.

Non-asbestos friction facing standard.

Flywheel drive ring and operating lever.

Service & Operation Manual containing installation instructions

DEFINITION:

A = Ball bearing throw out collar.

B = Bronze throw out collar.

L = Long shaft (Industry standard length)

HD = Sintered iron metallic facings.

8 = 80mm (307) pilot bearing.

10 = 100mm (300) pilot bearing.

*Manufacturers names, symbols and numbers are for reference purposes only and do not imply manufacturing origin.